

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A ~~method~~ computer-readable storage medium storing a program for reformatting binary image data, the binary image data transmitted from an external source outside an apparatus into which the computer-readable storage medium is installed, the program comprising the sequential steps of:  

receiving binary image data from the external source;  
converting ~~source~~ the binary image data into gray scale image data;  
segmenting the converted gray scale image data into a first plane having high spatial frequency gray scale image data and a second plane having low spatial frequency gray scale image data; and  
  
separately compressing the high spatial frequency gray scale image data in the first plane and the low spatial frequency gray scale image data in the second plane.
2. (Currently Amended) The ~~method~~ program of claim 1, wherein segmenting gray scale image data includes segmenting the gray scale image data into a plurality of blocks ~~based on gray scale levels of the gray scale image data.~~ before segmenting pixels in the blocks into the first plane and the second plane.
3. (Currently Amended) The ~~method~~ program of claim 1, further comprising:  

enhancing the low spatial frequency gray scale image data in the second plane.
- 4-8. (Canceled)
9. (Currently Amended) An apparatus to reformat binary image data, the binary image data transmitted from an external source outside the apparatus, the program elements comprising:

a converter that receives binary image data from the external source to convert  
source binary image data into gray scale image data;

a segmentor to segment the converted gray scale image data into high spatial  
frequency gray scale image data in a first plane and low spatial frequency gray scale image  
data in a second plane;

a first compressor to compress the high spatial frequency gray scale image data  
in the first plane; and

a second compressor to compress the low spatial frequency gray scale image  
data in the second ~~plane~~ plane;

wherein the converter, segmentor, first compressor and second compressor are  
implemented in software that is part of a program stored on a computer-readable storage  
medium installed in the apparatus, or in hardware.

10. (Currently Amended) The apparatus of claim 9, wherein the segmentor  
segments the gray scale image data into a plurality of blocks ~~based on gray scale levels of the  
gray scale image data~~ before segmenting pixels in the blocks into the first plane and the  
second plane.

11. (Original) The apparatus of claim 9, further comprising:  
a filter to enhance the low spatial frequency gray scale image data in the  
second plane.

12. (Original) A marking device incorporating the apparatus of claim 9.

13. (Original) A digital photocopier incorporating the apparatus of claim 9.

14. (Original) A stand alone document scanner or a multifunctional device  
incorporating the apparatus of claim 9.

15-20. (Canceled)

21. (New) A computer-readable storage medium storing a program for reformatting binary image data, the binary image data coming from an external source outside an apparatus into which the computer-readable storage medium is installed, the program comprising the steps of:

receiving binary data from the external source;

converting the binary data into gray scale image data;

segmenting the gray scale image data into a selector plane and a background plane;

scaling the gray scale image data in the background plane;

applying an enhancement filter or a tonal correction to the gray scale image data in the background plane; and

separately compressing the gray scale image data in the background plane using JPEG compression and the gray scale image data in the text plane using G4 compression.